Click to verify

×Sorry to interruptCSS Error ×Sorry to interruptCSS Error Share — copy and redistribute the material in any medium or format for any purpose, even commercially. Adapt — remix, transform, and build upon the material for any purpose, even commercially. The licensor cannot revoke these freedoms as long as you follow the license terms. Attribution — You must give appropriate credit , provide a link to the license, and indicate if changes were made . You may do so in any reasonable manner, but not in any way that suggests the licensor endorses you or your use. ShareAlike — If you remix, transform, or build upon the material, you must distribute your contributions under the same license as the original. No additional restrictions — You may not apply legal terms or technological measures that legally restrict others from doing anything the license permits. You do not have to comply with the license for elements of the material in the public domain or where your use is permitted by an applicable exception or limitation . No warranties are given. The license may not give you all of the permissions necessary for your intended use. For example, other rights such as publicity, privacy, or moral rights may limit how you use the material. View the manual for the Zebra DS8178 here, for free. This manual comes under the category barcode reader and has been rated by 1 people with an average of a 7.5. This manual is available in the following languages: English. Do you have a question about the Zebra DS8178 or do you need help?Ask your question hereBelow you will find the product specifications and the manual specifications of the Zebra DS8178.The Zebra DS8178 is a handheld barcode reader with dimensions measuring 168 millimeters in height, 107 millimeters in depth, and 66 millimeters in width. With a weight of 235.3 grams, it is relatively lightweight. The reader operates at a wavelength of 617 nanometers and utilizes a photo diode sensor type. Rated with an International Protection (IP) code of IP42, the DS8178 provides limited protection against dust and water. It is designed to be reliable and durable, ensuring longevity in various environments. As a handheld device, the Zebra DS8178 is specifically created for barcode scanning purposes. Equipped with advanced technology, it is capable of accurately scanning barcodes of different types. Potential areas of use for this barcode reader include retail, manufacturing, healthcare, and logistics, among others. Designed to meet the demands of various industries, the DS8178 is suitable for both indoor and outdoor applications. The Zebra DS8178 excels in providing accurate barcode scanning, contributing to increased efficiency in business operations. With its lightweight and compact design, it offers comfort and ease of use for extended periods. This barcode reader is ideal for individuals and organizations seeking a powerful yet portable scanning device. Its reliable performance ensures barcode accuracy and enhances productivity in any working environment. In conclusion, the Zebra DS8178 is a compact and durable handheld barcode reader that excels in providing accurate scanning of various types of barcodes. With its lightweight design and advanced technology features, it offers comfort and efficiency for prolonged use in multiple industries.Operating temperature (T-T) 0 - 50 °CConnectivity technology Wired & WirelessPower source type BatteryBrandZebraModelDS8178 | DS8178-SR0F007ZZWKProductbarcode readersLanguageEnglishFiletypeUser manual (PDF)Product color BlackInternational Protection (IP) code IP42Housing material -Height 168 mmDepth 107 mmWidth 66 mmWeight 235.3 gWavelength 617 nmSensor type Photo diodeTilt reading angle 0 - 360 °Pitch reading angle 0 - 60 °Yaw reading angle 0 - 60 °Type Handheld bar code readerLinear (1D) barcodes supported -2D (matrix & stacked) barcodes supported -Scanner type 1D/2DWorking distance 610 mmOptical sensor resolution 1280 pixelsOperating temperature (T-T) 0 - 50 °CStorage temperature (T-T) -40 - 70 °COperating relative humidity (H-H) 5 - 95 %Connectivity technology Wired & WirelessStandard interfaces USB, RS-232, BluetoothBluetooth version 4.0Wireless range 100 mPC connection RS-232/USBPower source type BatteryBattery capacity 2500 mAhBattery technology Lithium-Ion (Li-Ion)Battery life 83 h show moreCan't find the answer to your question in the manual? You may find the answer to your question in the FAQs about the Zebra DS8178 below.To pair your Zebra DS8178, you can access the Bluetooth settings on your device and search for available devices. Once you find the DS8178, select it to establish the pairing.You can customize the scanning settings by scanning specific configuration barcodes. These barcodes contain commands to modify settings such as barcode type compatibility, prefix and suffix characters, and scanning modes.Yes, you can adjust the beeper volume of the DS8178 scanner. By scanning the appropriate barcodes in the user manual, you can set the volume to your desired level.Absolutely! The Zebra DS8178 barcode reader is compatible with iOS devices. Simply enable Bluetooth on your iOS device and follow the pairing instructions to connect the DS8178 effortlessly.To replace the battery of the DS8178, you can remove the battery door located on the back of the device. Inside, you will find the battery pack, which can be easily replaced by disconnecting the old battery and connecting the new one securely.The sensor type of the Zebra DS8178 is a photo diode. This ensures accurate scanning of barcodes for the user.The International Protection (IP) code of the Zebra DS8178 is IP42. This means that it is protected against dust ingress and is also resistant to dripping water when tilted at an angle up to 15 degrees.The Zebra DS8178 has both wired and wireless connectivity technology. This allows the user to choose the most convenient option for their specific needs.The Bluetooth version of the Zebra DS8178 is 4.0. This ensures a stable and reliable wireless connection for seamless barcode scanning.The wireless range of the Zebra DS8178 is 100 meters. This provides the user with flexibility and freedom of movement while scanning barcodes within a large area.The Zebra DS8178 has a weight of 235.3 g.The Zebra DS8178 has a height of 168 mm.The Zebra DS8178 has a width of 66 mm.The Zebra DS8178 has a depth of 107 mm.Yes, the manual of the Zebra DS8178 is available in English .Is your question not listed? Ask your question herePage 2View the manual for the Zebra DS8178 here, for free. This manual comes under the category barcode reader and has been rated by 1 people with an average of a 7.5. This manual is available in the following languages: English. Do you have a question about the Zebra DS8178 or do you need help?Ask your question hereBelow you will find the product specifications and the manual specifications of the Zebra DS8178.The Zebra DS8178 is a handheld barcode reader with dimensions measuring 168 millimeters in height, 107 millimeters in depth, and 66 millimeters in width. With a weight of 235.3 grams, it is relatively lightweight. The reader operates at a wavelength of 617 nanometers and utilizes a photo diode sensor type. Rated with an International Protection (IP) code of IP42, the DS8178 provides limited protection against dust and water. It is designed to be reliable and durable, ensuring longevity in various environments. As a handheld device, the Zebra DS8178 is specifically created for barcode scanning purposes. Equipped with advanced technology, it is capable of accurately scanning barcodes of different types. Potential areas of use for this barcode reader include retail, manufacturing, healthcare, and logistics, among others. Designed to meet the demands of various industries, the DS8178 is suitable for both indoor and outdoor applications. The Zebra DS8178 excels in providing accurate barcode scanning, contributing to increased efficiency in business operations. With its lightweight and compact design, it offers comfort and ease of use for extended periods. This barcode reader is ideal for individuals and organizations seeking a powerful yet portable scanning device. Its reliable performance ensures barcode accuracy and enhances productivity in any working environment. In conclusion, the Zebra DS8178 is a compact and durable handheld barcode reader that excels in providing accurate scanning of various types of barcodes. With its lightweight design and advanced technology features, it offers comfort and efficiency for prolonged use in multiple industries.Operating temperature (T-T) 0 - 50 °CConnectivity technology Wired & WirelessPower source type BatteryBrandZebraModelDS8178 | DS8178-SR0F007ZZWKProductbarcode readersLanguageEnglishFiletypeUser manual (PDF)Product color BlackInternational Protection (IP) code IP42Housing material -Height 168 mmDepth 107 mmWidth 66 mmWeight 235.3 gWavelength 617 nmSensor type Photo diodeTilt reading angle 0 - 360 °Pitch reading angle 0 - 60 °Yaw reading angle 0 - 60 °Type Handheld bar code readerLinear (1D) barcodes supported -2D (matrix & stacked) barcodes supported -Scanner type 1D/2DWorking distance 610 mmOptical sensor resolution 1280 pixelsOperating temperature (T-T) 0 - 50 °CStorage temperature (T-T) -40 - 70 °COperating relative humidity (H-H) 5 - 95 %Connectivity technology Wired & WirelessStandard interfaces USB, RS-232, BluetoothBluetooth version 4.0Wireless range 100 mPC connection RS-232/USBPower source type BatteryBattery capacity 2500 mAhBattery technology Lithium-Ion (Li-Ion)Battery life 83 h show moreCan't find the answer to your question in the manual? You may find the answer to your question in the FAQs about the Zebra DS8178 below.To pair your Zebra DS8178, you can access the Bluetooth settings on your device and search for available devices. Once you find the DS8178, select it to establish the pairing.You can customize the scanning settings by scanning specific configuration barcodes. These barcodes contain commands to modify settings such as barcode type compatibility, prefix and suffix characters, and scanning modes.Yes, you can adjust the beeper volume of the DS8178 scanner. By scanning the appropriate barcodes in the user manual, you can set the volume to your desired level.Absolutely! The Zebra DS8178 barcode reader is compatible with iOS devices. Simply enable Bluetooth on your iOS device and follow the pairing instructions to connect the DS8178 effortlessly.To replace the battery of the DS8178, you can remove the battery door located on the back of the device. Inside, you will find the battery pack, which can be easily replaced by disconnecting the old battery and connecting the new one securely.The sensor type of the Zebra DS8178 is a photo diode. This ensures accurate scanning of barcodes for the user.The International Protection (IP) code of the Zebra DS8178 is IP42. This means that it is protected against dust ingress and is also resistant to dripping water when tilted at an angle up to 15 degrees.The Zebra DS8178 has both wired and wireless connectivity technology. This allows the user to choose the most convenient option for their specific needs.The Bluetooth version of the Zebra DS8178 is 4.0. This ensures a stable and reliable wireless connection for seamless barcode scanning.The wireless range of the Zebra DS8178 is 100 meters. This provides the user with flexibility and freedom of movement while scanning barcodes within a large area.The Zebra DS8178 has a weight of 235.3 g.The Zebra DS8178 has a height of 168 mm.The Zebra DS8178 has a width of 66 mm.The Zebra DS8178 has a depth of 107 mm.Yes, the manual of the Zebra DS8178 is available in English .Is your question not listed? Ask your question herePage 3View the manual for the Zebra DS8178 here, for free. This manual comes under the category barcode reader and has been rated by 1 people with an average of a 7.5. This manual is available in the following languages: English. Do you have a question about the Zebra DS8178 or do you need help?Ask your question hereBelow you will find the product specifications and the manual specifications of the Zebra DS8178.The Zebra DS8178 is a handheld barcode reader with dimensions measuring 168 millimeters in height, 107 millimeters in depth, and 66 millimeters in width. With a weight of 235.3 grams, it is relatively lightweight. The reader operates at a wavelength of 617 nanometers and utilizes a photo diode sensor type. Rated with an International Protection (IP) code of IP42, the DS8178 provides limited protection against dust and water. It is designed to be reliable and durable, ensuring longevity in various environments. As a handheld device, the Zebra DS8178 is specifically created for barcode scanning purposes. Equipped with advanced technology, it is capable of accurately scanning barcodes of different types. Potential areas of use for this barcode reader include retail, manufacturing, healthcare, and logistics, among others. Designed to meet the demands of various industries, the DS8178 is suitable for both indoor and outdoor applications. The Zebra DS8178 excels in providing accurate barcode scanning, contributing to increased efficiency in business operations. With its lightweight and compact design, it offers comfort and ease of use for extended periods. This barcode reader is ideal for individuals and organizations seeking a powerful yet portable scanning device. Its reliable performance ensures barcode accuracy and enhances productivity in any working environment. In conclusion, the Zebra DS8178 is a compact and durable handheld barcode reader that excels in providing accurate scanning of various types of barcodes. With its lightweight design and advanced technology features, it offers comfort and efficiency for prolonged use in multiple industries.Operating temperature (T-T) 0 - 50 °CConnectivity technology Wired & WirelessPower source type BatteryBrandZebraModelDS8178 | DS8178-SR0F007ZZWKProductbarcode readersLanguageEnglishFiletypeUser manual (PDF)Product color BlackInternational Protection (IP) code IP42Housing material -Height 168 mmDepth 107 mmWidth 66 mmWeight 235.3 gWavelength 617 nmSensor type Photo diodeTilt reading angle 0 - 360 °Pitch reading angle 0 - 60 °Yaw reading angle 0 - 60 °Type Handheld bar code readerLinear (1D) barcodes supported -2D (matrix & stacked) barcodes supported -Scanner type 1D/2DWorking distance 610 mmOptical sensor resolution 1280 pixelsOperating temperature (T-T) 0 - 50 °CStorage temperature (T-T) -40 - 70 °COperating relative humidity (H-H) 5 - 95 %Connectivity technology Wired & WirelessStandard interfaces USB, RS-232, BluetoothBluetooth version 4.0Wireless range 100 mPC connection RS-232/USBPower source type BatteryBattery capacity 2500 mAhBattery technology Lithium-Ion (Li-Ion)Battery life 83 h show moreCan't find the answer to your question in the manual? You may find the answer to your question in the FAQs about the Zebra DS8178 below.To pair your Zebra DS8178, you can access the Bluetooth settings on your device and search for available devices. Once you find the DS8178, select it to establish the pairing.You can customize the scanning settings by scanning specific configuration barcodes. These barcodes contain commands to modify settings such as barcode type compatibility, prefix and suffix characters, and scanning modes.Yes, you can adjust the beeper volume of the DS8178 scanner. By scanning the appropriate barcodes in the user manual, you can set the volume to your desired level.Absolutely! The Zebra DS8178 barcode reader is compatible with iOS devices. Simply enable Bluetooth on your iOS device and follow the pairing instructions to connect the DS8178 effortlessly.To replace the battery of the DS8178, you can remove the battery door located on the back of the device. Inside, you will find the battery pack, which can be easily replaced by disconnecting the old battery and connecting the new one securely.The sensor type of the Zebra DS8178 is a photo diode. This ensures accurate scanning of barcodes for the user.The International Protection (IP) code of the Zebra DS8178 is IP42. This means that it is protected against dust ingress and is also resistant to dripping water when tilted at an angle up to 15 degrees.The Zebra DS8178 has both wired and wireless connectivity technology. This allows the user to choose the most convenient option for their specific needs.The Bluetooth version of the Zebra DS8178 is 4.0. This ensures a stable and reliable wireless connection for seamless barcode scanning.The wireless range of the Zebra DS8178 is 100 meters. This provides the user with flexibility and freedom of movement while scanning barcodes within a large area.The Zebra DS8178 has a weight of 235.3 g.The Zebra DS8178 has a height of 168 mm.The Zebra DS8178 has a width of 66 mm.The Zebra DS8178 has a depth of 107 mm.Yes, the manual of the Zebra DS8178 is available in English .Is your question not listed? Ask your question herePage 4No part of this publication may be reproduced or used in any form, or by any electrical or mechanical means, without permission in writing from Zebra. This includes electronic or mechanical means, such as photocopying, recording, or information storage and retrieval systems. The material in this manual is subject to change The software is provided strictly on an “as is” basis. All software, including firmware, furnished to the user is on a licensed basis. Zebra grants to the user a non-transferable and non-exclusive license to use each software or firmware program delivered hereunder (licensed program). Except as noted below, such license may not be assigned, sublicensed, or otherwise transferred by the user without prior written consent of Zebra. No right to copy a licensed program in whole or in part is granted, except as permitted under copyright law. The user shall a derivative work from a licensed program, or use a licensed program in a network without written permission hereunder, and to include the same on any authorized copies it makes, in whole or in part. The user agrees not Zebra reserves the right to make changes to any software or product to improve reliability, function, or design.Zebra does not assume any product liability arising out of, or in connection with, the application or use of any No license is granted, either expressly or by implication, estoppel, or otherwise under any Zebra Technologies Corporation, intellectual property rights. An implied license only exists for equipment, circuits, and subsystems Page 5View the manual for the Zebra DS8178 here, for free. This manual comes under the category barcode reader and has been rated by 1 people with an average of a 7.5. This manual is available in the following languages: English. Do you have a question about the Zebra DS8178 or do you need help?Ask your question hereBelow you will find the product specifications and the manual specifications of the Zebra DS8178.The Zebra DS8178 is a handheld barcode reader with dimensions measuring 168 millimeters in height, 107 millimeters in depth, and 66 millimeters in width. With a weight of 235.3 grams, it is relatively lightweight. The reader operates at a wavelength of 617 nanometers and utilizes a photo diode sensor type. Rated with an International Protection (IP) code of IP42, the DS8178 provides limited protection against dust and water. It is designed to be reliable and durable, ensuring longevity in various environments. As a handheld device, the Zebra DS8178 is specifically created for barcode scanning purposes. Equipped with advanced technology, it is capable of accurately scanning barcodes of different types. Potential areas of use for this barcode reader include retail, manufacturing, healthcare, and logistics, among others. Designed to meet the demands of various industries, the DS8178 is suitable for both indoor and outdoor applications. The Zebra DS8178 excels in providing accurate barcode scanning, contributing to increased efficiency in business operations. With its lightweight and compact design, it offers comfort and ease of use for extended periods. This barcode reader is ideal for individuals and organizations seeking a powerful yet portable scanning device. Its reliable performance ensures barcode accuracy and enhances productivity in any working environment. In conclusion, the Zebra DS8178 is a compact and durable handheld barcode reader that excels in providing accurate scanning of various types of barcodes. With its lightweight design and advanced technology features, it offers comfort and efficiency for prolonged use in multiple industries.Operating temperature (T-T) 0 - 50 °CConnectivity technology Wired & WirelessPower source type BatteryBrandZebraModelDS8178 | DS8178-SR0F007ZZWKProductbarcode readersLanguageEnglishFiletypeUser manual (PDF)Product color BlackInternational Protection (IP) code IP42Housing material -Height 168 mmDepth 107 mmWidth 66 mmWeight 235.3 gWavelength 617 nmSensor type Photo diodeTilt reading angle 0 - 360 °Pitch reading angle 0 - 60 °Yaw reading angle 0 - 60 °Type Handheld bar code readerLinear (1D) barcodes supported -2D (matrix & stacked) barcodes supported -Scanner type 1D/2DWorking distance 610 mmOptical sensor resolution 1280 pixelsOperating temperature (T-T) 0 - 50 °CStorage temperature (T-T) -40 - 70 °COperating relative humidity (H-H) 5 - 95 %Connectivity technology Wired & WirelessStandard interfaces USB, RS-232, BluetoothBluetooth version 4.0Wireless range 100 mPC connection RS-232/USBPower source type BatteryBattery capacity 2500 mAhBattery technology Lithium-Ion (Li-Ion)Battery life 83 h show moreCan't find the answer to your question in the manual? You may find the answer to your question in the FAQs about the Zebra DS8178 below.To pair your Zebra DS8178, you can access the Bluetooth settings on your device and search for available devices. Once you find the DS8178, select it to establish the pairing.You can customize the scanning settings by scanning specific configuration barcodes. These barcodes contain commands to modify settings such as barcode type compatibility, prefix and suffix characters, and scanning modes.Yes, you can adjust the beeper volume of the DS8178 scanner. By scanning the appropriate barcodes in the user manual, you can set the volume to your desired level.Absolutely! The Zebra DS8178 barcode reader is compatible with iOS devices. Simply enable Bluetooth on your iOS device and follow the pairing instructions to connect the DS8178 effortlessly.To replace the battery of the DS8178, you can remove the battery door located on the back of the device. Inside, you will find the battery pack, which can be easily replaced by disconnecting the old battery and connecting the new one securely.The sensor type of the Zebra DS8178 is a photo diode. This ensures accurate scanning of barcodes for the user.The International Protection (IP) code of the Zebra DS8178 is IP42. This means that it is protected against dust ingress and is also resistant to dripping water when tilted at an angle up to 15 degrees.The Zebra DS8178 has both wired and wireless connectivity technology. This allows the user to choose the most convenient option for their specific needs.The Bluetooth version of the Zebra DS8178 is 4.0. This ensures a stable and reliable wireless connection for seamless barcode scanning.The wireless range of the Zebra DS8178 is 100 meters. This provides the user with flexibility and freedom of movement while scanning barcodes within a large area.The Zebra DS8178 has a weight of 235.3 g.The Zebra DS8178 has a height of 168 mm.The Zebra DS8178 has a width of 66 mm.The Zebra DS8178 has a depth of 107 mm.Yes, the manual of the Zebra DS8178 is available in English .Is your question not listed? Ask your question herePage 6View the manual for the Zebra DS8178 here, for free. This manual comes under the category barcode reader and has been rated by 1 people with an average of a 7.5. This manual is available in the following languages: English. Do you have a question about the Zebra DS8178 or do you need help?Ask your question hereBelow you will find the product specifications and the manual specifications of the Zebra DS8178.The Zebra DS8178 is a handheld barcode reader with dimensions measuring 168 millimeters in height, 107 millimeters in depth, and 66 millimeters in width. With a weight of 235.3 grams, it is relatively lightweight. The reader operates at a wavelength of 617 nanometers and utilizes a photo diode sensor type. Rated with an International Protection (IP) code of IP42, the DS8178 provides limited protection against dust and water. It is designed to be reliable and durable, ensuring longevity in various environments. As a handheld device, the Zebra DS8178 is specifically created for barcode scanning purposes. Equipped with advanced technology, it is capable of accurately scanning barcodes of different types. Potential areas of use for this barcode reader include retail, manufacturing, healthcare, and logistics, among others. Designed to meet the demands of various industries, the DS8178 is suitable for both indoor and outdoor applications. The Zebra DS8178 excels in providing accurate barcode scanning, contributing to increased efficiency in business operations. With its lightweight and compact design, it offers comfort and ease of use for extended periods. This barcode reader is ideal for individuals and organizations seeking a powerful yet portable scanning device. Its reliable performance ensures barcode accuracy and enhances productivity in any working environment. In conclusion, the Zebra DS8178 is a compact and durable handheld barcode reader that excels in providing accurate scanning of various types of barcodes. With its lightweight design and advanced technology features, it offers comfort and efficiency for prolonged use in multiple industries.Operating temperature (T-T) 0 - 50 °CConnectivity technology Wired & WirelessPower source type BatteryBrandZebraModelDS8178 | DS8178-SR0F007ZZWKProductbarcode readersLanguageEnglishFiletypeUser manual (PDF)Product color BlackInternational Protection (IP) code IP42Housing material -Height 168 mmDepth 107 mmWidth 66 mmWeight 235.3 gWavelength 617 nmSensor type Photo diodeTilt reading angle 0 - 360 °Pitch reading angle 0 - 60 °Yaw reading angle 0 - 60 °Type Handheld bar code readerLinear (1D) barcodes supported -2D (matrix & stacked) barcodes supported -Scanner type 1D/2DWorking distance 610 mmOptical sensor resolution 1280 pixelsOperating temperature (T-T) 0 - 50 °CStorage temperature (T-T) -40 - 70 °COperating relative humidity (H-H) 5 - 95 %Connectivity technology Wired & WirelessStandard interfaces USB, RS-232, BluetoothBluetooth version 4.0Wireless range 100 mPC connection RS-232/USBPower source type BatteryBattery capacity 2500 mAhBattery technology Lithium-Ion (Li-Ion)Battery life 83 h show moreCan't find the answer to your question in the manual? You may find the answer to your question in the FAQs about the Zebra DS8178 below.To pair your Zebra DS8178, you can access the Bluetooth settings on your device and search for available devices. Once you find the DS8178, select it to establish the pairing.You can customize the scanning settings by scanning specific configuration barcodes. These barcodes contain commands to modify settings such as barcode type compatibility, prefix and suffix characters, and scanning modes.Yes, you can adjust the beeper volume of the DS8178 scanner. By scanning the appropriate barcodes in the user manual, you can set the volume to your desired level.Absolutely! The Zebra DS8178 barcode reader is compatible with iOS devices. Simply enable Bluetooth on your iOS device and follow the pairing instructions to connect the DS8178 effortlessly.To replace the battery of the DS8178, you can remove the battery door located on the back of the device. Inside, you will find the battery pack, which can be easily replaced by disconnecting the old battery and connecting the new one securely.The sensor type of the Zebra DS8178 is a photo diode. This ensures accurate scanning of barcodes for the user.The International Protection (IP) code of the Zebra DS8178 is IP42. This means that it is protected against dust ingress and is also resistant to dripping water when tilted at an angle up to 15 degrees.The Zebra DS8178 has both wired and wireless connectivity technology. This allows the user to choose the most convenient option for their specific needs.The Bluetooth version of the Zebra DS8178 is 4.0. This ensures a stable and reliable wireless connection for seamless barcode scanning.The wireless range of the Zebra DS8178 is 100 meters. This provides the user with flexibility and freedom of movement while scanning barcodes within a large area.The Zebra DS8178 has a weight of 235.3 g.The Zebra DS8178 has a height of 168 mm.The Zebra DS8178 has a width of 66 mm.The Zebra DS8178 has a depth of 107 mm.Yes, the manual of the Zebra DS8178 is available in English .Is your question not listed? Ask your question herePage 7View the manual for the Zebra DS8178 here, for free. This manual comes under the category barcode reader and has been rated by 1 people with an average of a 7.5. This manual is available in the following languages: English. Do you have a question about the Zebra DS8178 or do you need help?Ask your question hereBelow you will find the product specifications and the manual specifications of the Zebra DS8178.The Zebra DS8178 is a handheld barcode reader with dimensions measuring 168 millimeters in height, 107 millimeters in depth, and 66 millimeters in width. With a weight of 235.3 grams, it is relatively lightweight. The reader operates at a wavelength of 617 nanometers and utilizes a photo diode sensor type. Rated with an International Protection (IP) code of IP42, the DS8178 provides limited protection against dust and water. It is designed to be reliable and durable, ensuring longevity in various environments. As a handheld device, the Zebra DS8178 is specifically created for barcode scanning purposes. Equipped with advanced technology, it is capable of accurately scanning barcodes of different types. Potential areas of use for this barcode reader include retail, manufacturing, healthcare, and logistics, among others. Designed to meet the demands of various industries, the DS8178 is suitable for both indoor and outdoor applications. The Zebra DS8178 excels in providing accurate barcode scanning, contributing to increased efficiency in business operations. With its lightweight and compact design, it offers comfort and ease of use for extended periods. This barcode reader is ideal for individuals and organizations seeking a powerful yet portable scanning device. Its reliable performance ensures barcode accuracy and enhances productivity in any working environment. In conclusion, the Zebra DS8178 is a compact and durable handheld barcode reader that excels in providing accurate scanning of various types of barcodes. With its lightweight design and advanced technology features, it offers comfort and efficiency for prolonged use in multiple industries.Operating temperature (T-T) 0 - 50 °CConnectivity technology Wired & WirelessPower source type BatteryBrandZebraModelDS8178 | DS8178-SR0F007ZZWKProductbarcode readersLanguageEnglishFiletypeUser manual (PDF)Product color BlackInternational Protection (IP) code IP42Housing material -Height 168 mmDepth 107 mmWidth 66 mmWeight 235.3 gWavelength 617 nmSensor type Photo diodeTilt reading angle 0 - 360 °Pitch reading angle 0 - 60 °Yaw reading angle 0 - 60 °Type Handheld bar code readerLinear (1D) barcodes supported -2D (matrix & stacked) barcodes supported -Scanner type 1D/2DWorking distance 610 mmOptical sensor resolution 1280 pixelsOperating temperature (T-T) 0 - 50 °CStorage temperature (T-T) -40 - 70 °COperating relative humidity (H-H) 5 - 95 %Connectivity technology Wired & WirelessStandard interfaces USB, RS-232, BluetoothBluetooth version 4.0Wireless range 100 mPC connection RS-232/USBPower source type BatteryBattery capacity 2500 mAhBattery technology Lithium-Ion (Li-Ion)Battery life 83 h show moreCan't find the answer to your question in the manual? You may find the answer to your question in the FAQs about the Zebra DS8178 below.To pair your Zebra DS8178, you can access the Bluetooth settings on your device and search for available devices. Once you find the DS8178, select it to establish the pairing.You can customize the scanning settings by scanning specific configuration barcodes. These barcodes contain commands to modify settings such as barcode type compatibility, prefix and suffix characters, and scanning modes.Yes, you can adjust the beeper volume of the DS8178 scanner. By scanning the appropriate barcodes in the user manual, you can set the volume to your desired level.Absolutely! The Zebra DS8178 barcode reader is compatible with iOS devices. Simply enable Bluetooth on your iOS device and follow the pairing instructions to connect the DS8178 effortlessly.To replace the battery of the DS8178, you can remove the battery door located on the back of the device. Inside, you will find the battery pack, which can be easily replaced by disconnecting the old battery and connecting the new one securely.The sensor type of the Zebra DS8178 is a photo diode. This ensures accurate scanning of barcodes for the user.The International Protection (IP) code of the Zebra DS8178 is IP42. This means that it is protected against dust ingress and is also resistant to dripping water when tilted at an angle up to 15 degrees.The Zebra DS8178 has both wired and wireless connectivity technology. This allows the user to choose the most convenient option for their specific needs.The Bluetooth version of the Zebra DS8178 is 4.0. This ensures a stable and reliable wireless connection for seamless barcode scanning.The wireless range of the Zebra DS8178 is 100 meters. This provides the user with flexibility and freedom of movement while scanning barcodes within a large area.The Zebra DS8178 has a weight of 235.3 g.The Zebra DS8178 has a height of 168 mm.The Zebra DS8178 has a width of 66 mm.The Zebra DS8178 has a depth of 107 mm.Yes, the manual of the Zebra DS8178 is available in English .Is your question not listed? Ask your question herePage 8View the manual for the Zebra DS8178 here, for free. This manual comes under the category barcode reader and has been rated by 1 people with an average of a 7.5. This manual is available in the following languages: English. Do you have a question about the Zebra DS8178 or do you need help?Ask your question hereBelow you will find the product specifications and the manual specifications of the Zebra DS8178.The Zebra DS8178 is a handheld barcode reader with dimensions measuring 168 millimeters in height, 107 millimeters in depth, and 66 millimeters in width. With a weight of 235.3 grams, it is relatively lightweight. The reader operates at a wavelength of 617 nanometers and utilizes a photo diode sensor type. Rated with an International Protection (IP) code of IP42, the DS8178 provides limited protection against dust and water. It is designed to be reliable and durable, ensuring longevity in various environments. As a handheld device, the Zebra DS8178 is specifically created for barcode scanning purposes. Equipped with advanced technology, it is capable of accurately scanning barcodes of different types. Potential areas of use for this barcode reader include retail, manufacturing, healthcare, and logistics, among others. Designed to meet the demands of various industries, the DS8178 is suitable for both indoor and outdoor applications. The Zebra DS8178 excels in providing accurate barcode scanning, contributing to increased efficiency in business operations. With its lightweight and compact design, it offers comfort and ease of use for extended periods. This barcode reader is ideal for individuals and organizations seeking a powerful yet portable scanning device. Its reliable performance ensures barcode accuracy and enhances productivity in any working environment. In conclusion, the Zebra DS8178 is a compact and durable handheld barcode reader that excels in providing accurate scanning of various types of barcodes. With its lightweight design and advanced technology features, it offers comfort and efficiency for prolonged use in multiple industries.Operating temperature (T-T) 0 - 50 °CConnectivity technology Wired & WirelessPower source type BatteryBrandZebraModelDS8178 | DS8178-SR0F007ZZWKProductbarcode readersLanguageEnglishFiletypeUser manual (PDF)Product color BlackInternational Protection (IP) code IP42Housing material -Height 168 mmDepth 107 mmWidth 66 mmWeight 235.3 gWavelength 617 nmSensor type Photo diodeTilt reading angle 0 - 360 °Pitch reading angle 0 - 60 °Yaw reading angle 0 - 60 °Type Handheld bar code readerLinear (1D) barcodes supported -2D (matrix & stacked) barcodes supported -Scanner type 1D/2DWorking distance 610 mmOptical sensor resolution 1280 pixelsOperating temperature (T-T) 0 - 50 °CStorage temperature (T-T) -40 - 70 °COperating relative humidity (H-H) 5 - 95 %Connectivity technology Wired & WirelessStandard interfaces USB, RS-232, BluetoothBluetooth version 4.0Wireless range 100 mPC connection RS-232/USBPower source type BatteryBattery capacity 2500 mAhBattery technology Lithium-Ion (Li-Ion)Battery life 83 h show moreCan't find the answer to your question in the manual? You may find the answer to your question in the FAQs about the Zebra DS8178 below.To pair your Zebra DS8178, you can access the Bluetooth settings on your device and search for available devices. Once you find the DS8178, select it to establish the pairing.You can customize the scanning settings by scanning specific configuration barcodes. These barcodes contain commands to modify settings such as barcode type compatibility, prefix and suffix characters, and scanning modes.Yes, you can adjust the beeper volume of the DS8178 scanner. By scanning the appropriate barcodes in the user manual, you can set the volume to your desired level.Absolutely! The Zebra DS8178 barcode reader is compatible with iOS devices. Simply enable Bluetooth on your iOS device and follow the pairing instructions to connect the DS8178 effortlessly.To replace the battery of the DS8178, you can remove the battery door located on the back of the device. Inside, you will find the battery pack, which can be easily replaced by disconnecting the old battery and connecting the new one securely.The sensor type of the Zebra DS8178 is a photo diode. This ensures accurate scanning of barcodes for the user.The International Protection (IP) code of the Zebra DS8178 is IP42. This means that it is protected against dust ingress and is also resistant to dripping water when tilted at an angle up to 15 degrees.The Zebra DS8178 has both wired and wireless connectivity technology. This allows the user to choose the most convenient option for their specific needs.The Bluetooth version of the Zebra DS8178 is 4.0. This ensures a stable and reliable wireless connection for seamless barcode scanning.The wireless range of the Zebra DS8178 is 100 meters. This provides the user with flexibility and freedom of movement while scanning barcodes within a large area.The Zebra DS8178 has a weight of 235.3 g.The Zebra DS8178 has a height of 168 mm.The Zebra DS8178 has a width of 66 mm.The Zebra DS8178 has a depth of 107 mm.Yes, the manual of the Zebra DS8178 is available in English .Is your question not listed? Ask your question herePage 9View the manual for the Zebra DS8178 here, for free. This manual comes under the category barcode reader and has been rated by 1 people with an average of a 7.5. This manual is available in the following languages: English. Do you have a question about the Zebra DS8178 or do you need help?Ask your question hereBelow you will find the product specifications and the manual specifications of the Zebra DS8178.The Zebra DS8178 is a handheld barcode reader with dimensions measuring 168 millimeters in height, 107 millimeters in depth, and 66 millimeters in width. With a weight of 235.3 grams, it is relatively lightweight. The reader operates at a wavelength of 617 nanometers and utilizes a photo diode sensor type. Rated with an International Protection (IP) code of IP42, the DS8178 provides limited protection against dust and water. It is designed to be reliable and durable, ensuring longevity in various environments. As a handheld device, the Zebra DS8178 is specifically created for barcode scanning purposes. Equipped with advanced technology, it is capable of accurately scanning barcodes of different types. Potential areas of use for this barcode reader include retail, manufacturing, healthcare, and logistics, among others. Designed to meet the demands of various industries, the DS8178 is suitable for both indoor and outdoor applications. The Zebra DS8178 excels in providing accurate barcode scanning, contributing to increased efficiency in business operations. With its lightweight and compact design, it offers comfort and ease of use for extended periods. This barcode reader is ideal for individuals and organizations seeking a powerful yet portable scanning device. Its reliable performance ensures barcode accuracy and enhances productivity in any working environment. In conclusion, the Zebra DS8178 is a compact and durable handheld barcode reader that excels in providing accurate scanning of various types of barcodes. With its lightweight design and advanced technology features, it offers comfort and efficiency for prolonged use in multiple industries.Operating temperature (T-T) 0 - 50 °CConnectivity technology Wired & WirelessPower source type BatteryBrandZebraModelDS8178 | DS8178-SR0F007ZZWKProductbarcode readersLanguageEnglishFiletypeUser manual (PDF)Product color BlackInternational Protection (IP) code IP42Housing material -Height 168 mmDepth 107 mmWidth 66 mmWeight 235.3 gWavelength 617 nmSensor type Photo diodeTilt reading angle 0 - 360 °Pitch reading angle 0 - 60 °Yaw reading angle 0 - 60 °Type Handheld bar code readerLinear (1D) barcodes supported -2D (matrix & stacked) barcodes supported -Scanner type 1D/2DWorking distance 610 mmOptical sensor resolution 1280 pixelsOperating temperature (T-T) 0 - 50 °CStorage temperature (T-T) -40 - 70 °COperating relative humidity (H-H) 5 - 95 %Connectivity technology Wired & WirelessStandard interfaces USB, RS-232, BluetoothBluetooth version 4.0Wireless range 100 mPC connection RS-232/USBPower source type BatteryBattery capacity 2500 mAhBattery technology Lithium-Ion (Li-Ion)Battery life 83 h show moreCan't find the answer to your question in the manual? You may find the answer to your question in the FAQs about the Zebra DS8178 below.To pair your Zebra DS8178, you can access the Bluetooth settings on your device and search for available devices. Once you find the DS8178, select it to establish the pairing.You can customize the scanning settings by scanning specific configuration barcodes. These barcodes contain commands to modify settings such as barcode type compatibility, prefix and suffix characters, and scanning modes.Yes, you can adjust the beeper volume of the DS8178 scanner. By scanning the appropriate barcodes in the user manual, you can set the volume to your desired level.Absolutely! The Zebra DS8178 barcode reader is compatible with iOS devices. Simply enable Bluetooth on your iOS device and follow the pairing instructions to connect the DS8178 effortlessly.To replace the battery of the DS8178, you can remove the battery door located on the back of the device. Inside, you will find the battery pack, which can be easily replaced by disconnecting the old battery and connecting the new one securely.The sensor type of the Zebra DS8178 is a photo diode. This ensures accurate scanning of barcodes for the user.The International Protection (IP) code of the Zebra DS8178 is IP42. This means that it is protected against dust ingress and is also resistant to dripping water when tilted at an angle up to 15 degrees.The Zebra DS8178 has both wired and wireless connectivity technology. This allows the user to choose the most convenient option for their specific needs.The Bluetooth version of the Zebra DS8178 is 4.0. This ensures a stable and reliable wireless connection for seamless barcode scanning.The wireless range of the Zebra DS8178 is 100 meters. This provides the user with flexibility and freedom of movement while scanning barcodes within a large area.The Zebra DS8178 has a weight of 235.3 g.The Zebra DS8178 has a height of 168 mm.The Zebra DS8178 has a width of 66 mm.The Zebra DS8178 has a depth of 107 mm.Yes, the manual of the Zebra DS8178 is available in English .Is your question not listed? Ask your question herePage 10View the manual for the Zebra DS8178 here, for free. This man

..... 10-13Host Serial Response Time-out ..... 10-15RTS Line State ..... 10-16Beep on ..... 10-16Intercharacter Delay ..... 10-17Nixdorf Beep/LED Options ..... 10-18Ignore Unknown Characters ..... 10-18ASCII Character Set for RS-232
..... 10-18Introduction ..... 11-1Connecting to an IBM 468X/469X Host ..... 11-2IBM Parameter Defaults
..... 11-3IBM 468X/469X Host Parameters ..... 11-4Port Address ..... 11-4Convert Unknown to Code 39
..... 11-5RS-485 Beep Directive ..... 11-5RS-485 Bar Code Configuration Directive ..... 11-6IBM-485 Specification Version ..... 11-6Introduction ..... 12-1Connecting a Keyboard Wedge Interface ..... 12-2Keyboard Wedge Parameter Defaults ..... 12-3Keyboard Wedge Host Parameters
..... 12-4Keyboard Wedge Host Types ..... 12-4Ignore Unknown Characters ..... 12-4Keystroke Delay ..... 12-5Intra-Keystroke Delay ..... 12-5Alternate Numeric Keypad Emulation ..... 12-6Quick Keypad Emulation ..... 12-6Simulated Caps Lock
..... 12-7Page 17Caps Lock Override ..... 12-7Convert Wedge Case ..... 12-8Function Key Mapping
..... 12-8FN1 Substitution ..... 12-9Send Make and Break ..... 12-9Keyboard Maps ..... 12-10ASCII Character Set for Keyboard Wedge ..... 12-10Introduction ..... 13-1Scanning Sequence Examples ..... 13-1Errors While Scanning
..... 13-2Symbology Parameter Defaults ..... 13-2Enable/Disable All Code Types 13-8UPC/EAN
..... 13-8Enable/Disable UPC-A ..... 13-8Enable/Disable UPC-E 13-9Enable/Disable UPC-E1
..... 13-9Enable/Disable EAN-8/JAN-8 ..... 13-10Enable/Disable EAN-13/JAN-13 ..... 13-10Enable/Disable Bookland EAN ..... 13-11User-Programmable Supplementals ..... 13-15UPC Reduced Quiet Zone ..... 13-17Transmit UPC-A Check Digit ..... 13-17Transmit UPC-E Check Digit
..... 13-18Transmit UPC-E1 Check Digit ..... 13-18UPC-A Preamble ..... 13-19UPC-E Preamble ..... 13-20UPC-E1 Preamble ..... 13-21Convert UPC-E to UPC-A ..... 13-22Convert UPC-E1 to UPC-A ..... 13-22EAN-8/JAN-8 Extend
..... 13-23Bookland ISBN Format ..... 13-23UCC Coupon Extended Code ..... 13-24Coupon Report ..... 13-24ISSN EAN ..... 13-25Code 128 ..... 13-25Enable/Disable Code 128 ..... 13-25Set Lengths for Code 128
..... 13-26Enable/Disable ISBT 128 ..... 13-28ISBT Concatenation ..... 13-29Check ISBT Table ..... 13-30ISBT Concatenation Redundancy ..... 13-30Code 128 Security Level ..... 13-31Code 128 Reduced Quiet Zone ..... 13-32Page 18Ignore Code 128
..... 13-32Code 39 ..... 13-33Enable/Disable Code 39 ..... 13-33Enable/Disable Trioptic Code 39 ..... 13-33Convert Code 39 to Code 32 ..... 13-34Code 32 Prefix ..... 13-34Set Lengths for Code 39 ..... 13-35Code 39 Check Digit Verification
..... 13-36Transmit Code 39 Check Digit ..... 13-36Code 39 Full ASCII Conversion ..... 13-37Code 39 Security Level ..... 13-38Code 39 Reduced Quiet Zone ..... 13-39Code 93 ..... 13-39Enable/Disable Code 93 ..... 13-39Set Lengths for Code 93
..... 13-40Code 11 ..... 13-41Code 11 ..... 13-41Set Lengths for Code 11 ..... 13-41Code 11 Check Digit Verification ..... 13-43Interleaved 2 of 5 (ITF) ..... 13-44Enable/Disable Interleaved 2 of 5 ..... 13-44Set Lengths for Interleaved 2 of 5
..... 13-44I 2 of 5 Check Digit Verification ..... 13-46Convert I 2 of 5 to EAN-13 ..... 13-47Febraban ..... 13-47I 2 of 5 Security Level ..... 13-48I 2 of 5 Reduced Quiet Zone ..... 13-49Discrete 2 of 5 (DTF) ..... 13-50Enable/Disable Discrete 2 of 5
..... 13-50Set Lengths for Discrete 2 of 5 ..... 13-50Codabar (NW - 7) ..... 13-52Enable/Disable Codabar ..... 13-52Set Lengths for Codabar ..... 13-52CLSI Editing ..... 13-54NOTIS Editing ..... 13-54Codabar Security Level
..... 13-55MSI ..... 13-56Enable/Disable MSI ..... 13-56Set Lengths for MSI
..... 13-57MSI Check Digits ..... 13-58Transmit MSI Check Digit(s) ..... 13-59MSI Check Digit Algorithm
..... 13-59MSI Reduced Quiet Zone ..... 13-60Chinese 2 of 5 ..... 13-61Enable/Disable Chinese 2 of 5 ..... 13-61Matrix 2 of 5 ..... 13-61Enable/Disable Matrix 2 of 5 ..... 13-61Set Lengths for Matrix 2 of 5 ..... 13-62Matrix 2 of 5 Check Digit
..... 13-63Page 19Transmit Matrix 2 of 5 Check Digit ..... 13-63Korean 3 of 5 ..... 13-64Enable/Disable Korean 3 of 5
..... 13-64Inverse 1D ..... 13-65GS1 DataBar ..... 13-66GS1 DataBar Stacked, GS1 DataBar Stacked Omnidirectional ..... 13-66GS1 DataBar Limited ..... 13-66Convert GS1 DataBar to UPC/EAN ..... 13-67GS1 DataBar Limited Margin Check ..... 13-68GS1 DataBar Security Level
..... 13-69Composite ..... 13-70Composite CC-C ..... 13-70Composite CC-A/B ..... 13-70Composite TLC-39 ..... 13-71Composite Inverse ..... 13-71UPC Composite Mode ..... 13-72Composite Beep Mode
..... 13-722D Symbologies ..... 13-74Enable/Disable PDF417 ..... 13-74Enable/Disable MicroPDF417
..... 13-74Code 128 Emulation ..... 13-74Data Matrix ..... 13-75GS1 Data Matrix ..... 13-75Data Matrix Inverse ..... 13-77Maxicode ..... 13-77QR Code ..... 13-78GS1 QR
..... 13-78MicroQR ..... 13-79Linked QR Mode 13-80Aztec
..... 13-81Aztec Inverse ..... 13-81Han Xin ..... 13-82Han Xin Inverse
..... 13-82Grid Matrix ..... 13-83Grid Matrix Inverse ..... 13-83Grid Matrix Mirror
..... 13-84DotCode ..... 13-84DotCode Inverse ..... 13-85DotCode Mirrored
..... 13-86DotCode Prioritize ..... 13-87Postal Codes ..... 13-87US Postnet
..... 13-87US Planet ..... 13-88Transmit US Postal Check Digit ..... 13-88UK Postal
..... 13-89Transmit UK Postal Check Digit ..... 13-89Japan Postal ..... 13-90Page 20Australia Post
..... 13-90Australia Post Format ..... 13-91Netherlands KIX Code ..... 13-92USPS 4CB/One Code/Intelligent Mail
..... 13-92UPU FICS Postal ..... 13-93Mailmark ..... 13-93Symbology-Specific Security Levels ..... 13-94Redundancy Level ..... 13-94Redundancy Level 1 ..... 13-94Redundancy Level 2 ..... 13-94Redundancy Level 3
..... 13-94Redundancy Level 4 ..... 13-95Security Level ..... 13-961D Quiet Zone Level ..... 13-97Intercharacter Gap Size ..... 13-98Report Version ..... 13-98Macro PDF Features ..... 13-99Flush Macro Buffer
..... 13-99Abort Macro PDF Entry ..... 13-99Introduction ..... 14-1The IDC Process
..... 14-1Bar Code Acceptance Test ..... 14-2Capture Region Determination ..... 14-2Image Post Processing
..... 14-3Data Transmission ..... 14-3PC Application and Programming Support 14-3Parameters
..... 14-4IDC Operating Mode ..... 14-5IDC Symbology ..... 14-6IDC X Coordinate
..... 14-7IDC Y Coordinate ..... 14-7IDC Width ..... 14-8IDC Height
..... 14-8IDC Aspect ..... 14-9IDC File Format Selector ..... 14-9IDC Bits Per Pixel
..... 14-10IDC JPEG Quality ..... 14-10IDC Find Box Outline ..... 14-11IDC Minimum Text Length
..... 14-11IDC Maximum Text Length ..... 14-12IDC Captured Image Brighten ..... 14-12IDC Captured Image Sharpen ..... 14-13IDC Border Type ..... 14-14IDC Delay Time ..... 14-15IDC Zoom Limit ..... 14-15Page 21IDC Maximum Rotation
..... 14-16Quick Start ..... 14-16Sample IDC Setup ..... 14-16IDC Demonstrations
..... 14-17Anchored Mode Demo ..... 14-17Free-Form Mode Demo ..... 14-18Linked Mode Demo ..... 14-18Other Suggestions ..... 14-18Quick Start Form ..... 14-19Introduction ..... 15-1Digimarc Symbology Selection
..... 15-1Picklist ..... 15-1Digimarc Digital Watermarks 15-2Introduction
..... 16-1Advanced Data Formatting (ADF) ..... 16-1Multicode Data Formatting (MDF) ..... 16-1MDF in Hands-Free Mode
..... 16-2MDF Best Practices ..... 16-3Preferred Symbol ..... 16-4Data Parsing
..... 16-5Introduction ..... 17-1Setting Parameters ..... 17-1Scanning Sequence Examples
..... 17-2Errors While Scanning ..... 17-2OCR Parameter Defaults ..... 17-2OCR Programming Parameters ..... 17-3OCR-A ..... 17-3OCR-A Variant ..... 17-4OCR-B ..... 17-5OCR-B Variant
..... 17-6MICR E13B ..... 17-10US Currency Serial Number ..... 17-11OCR Orientation
..... 17-11OCR Lines ..... 17-13OCR Minimum Characters ..... 17-13OCR Maximum Characters
..... 17-14OCR Subset ..... 17-14OCR Quiet Zone ..... 17-15OCR Template ..... 17-15Required Digit (9) ..... 17-16Required Alpha (A) ..... 17-16Optional Alphanumeric (1) ..... 17-16Page 22Optional Alpha (2)
..... 17-17Alpha or Digit (3) ..... 17-17Any Including Space & Reject (4) ..... 17-17Any except Space & Reject (5) ..... 17-18Optional Digit (7) ..... 17-18Digit or Fill (8) ..... 17-18Alpha or Fill (F) ..... 17-19Optional Space ( )
..... 17-19Optional Small Special (.) ..... 17-19Other Template Operators ..... 17-20Repeat Previous (R) ..... 17-24Multiple Templates ..... 17-25Template Examples ..... 17-25OCR Check Digit Modulus ..... 17-25OCR Check Digit Multiplier
..... 17-26OCR Check Digit Validation ..... 17-27None ..... 17-27Product Add Left to Right ..... 17-27Digit Add Left to Right ..... 17-28Digit Add Right to Left ..... 17-29Health Industry - HIBCC43 ..... 17-31Inverse OCR
..... 17-32OCR Redundancy ..... 17-33Introduction ..... 18-1Driver’s License Parsing
..... 18-2(Embedded Driver's License Parsing) ..... 18-3Embedded Driver's License Parsing Criteria - Code Type ..... 18-3Driver’s License Parse Field Bar Codes
..... 18-4AAMVA Parse Field Bar Codes ..... 18-7User Preferences ..... 18-17Set Default Parameter ..... 18-17Output Gender as M or F ..... 18-17Date Format ..... 18-18No Separator ..... 18-19Control Characters
..... 18-20Keyboard Characters ..... 18-26Parsing Rule Example ..... 18-41Embedded Driver's License Parsing ADF Example ..... 18-45Page 23Introduction ..... B-1USB, BT HID, and Keyboard Wedge Country Keyboard Types (Country Codes) ..... B-2Introduction ..... C-1Country Code Page Defaults
..... C-1Country Code Page Bar Codes ..... C-5Introduction ..... D-1CJK Control Parameters
..... D-2Unicode Output Control ..... D-2CJK Output Method to Windows Host ..... D-3Non-CJK UTF Bar Code Output
..... D-5Unicode/CJK Decode Setup with Windows Host ..... D-7Setting Up the Windows Registry Table for Unicode Universal Output ..... D-7Adding CJK IME on Windows ..... D-7Symbol Code Identifiers ..... E-1AIM Code Identifiers ..... E-3UPC/EAN F-1UPC-A, 100%
..... F-1UPC-A with 2-digit Add-on ..... F-1UPC-A with 5-digit Add-on F-2UPC-E
..... F-2UPC-E with 2-digit Add-on ..... F-2UPC-E with 5-digit Add-on F-3EAN-8
..... F-3EAN-13, 100% ..... F-3EAN-13 with 2-digit Add-on ..... F-4EAN-13 with 5-digit Add-on
..... F-4Code 128 ..... F-4GS1-128 ..... F-5Code 39
..... F-5Code 93 ..... F-5Code 11 with 2 Check Digits ..... F-6Page 24Interleaved 2 of 5
..... F-6MSI with 2 Check Digits ..... F-6Chinese 2 of 5 ..... F-7Matrix 2 of 5
..... F-7Korean 3 of 5 ..... F-7GS1 DataBar ..... F-8GS1 DataBar Truncated
..... F-8GS1 DataBar Stacked ..... F-8GS1 DataBar Stacked Omnidirectional ..... F-9GS1 DataBar Limited ..... F-9GS1 DataBar Expanded ..... F-10GS1 DataBar Expanded Stacked ..... F-102D Symbologies F-11PDF417
..... F-11Data Matrix ..... F-11GS1 Data Matrix F-12Maxicode
..... F-12QR Code ..... F-12GS1 QR F-13MicroQR
..... F-13Aztec ..... F-13Grid Matrix ..... F-14Han Xin
..... F-14Postal Codes ..... F-14US Postnet ..... F-14UK Postal
..... F-14Japan Postal ..... F-15Australian Post F-15OCR
..... F-16OCR-A ..... F-16OCR-B F-16MICR E13B
..... F-16US Currency ..... F-16Cancel ..... G-1Numeric Bar Codes
..... G-1Cancel ..... H-1Alphanumeric Bar Codes ..... H-1Page 25Functionality Supported via Radio Communication
..... J-2Introduction ..... K-1Code Structure ..... K-1Signature Capture Area ..... K-1CapCode Pattern Structure ..... K-2Start / Stop Patterns ..... K-2Dimensions ..... K-3Data Format
..... K-3Additional Capabilities ..... K-4Signature Boxes K-4Introduction
..... L-1Attributes ..... L-1Model Number ..... L-1Serial Number
..... L-1Date of Manufacture ..... L-2Date of First Programming ..... L-2Configuration Filename
..... L-2Beeper/LED ..... L-3Parameter Defaults ..... L-4Beep on Next Bootup ..... L-4Reboot ..... L-4Host Trigger Session ..... L-4Firmware Version ..... L-5Scankit Version
..... L-5ScanSpeed Analytics ..... L-5Introduction M-1Introduction
..... N-1Histogram Decode Information ..... N-1Image of Slowest Decoded Bar Code ..... N-5Page 26View the manual for the Zebra DS8178 here, for free. This manual comes under the category barcode reader and has been rated by 1 people with an average of a 7.5. This manual is available in the following languages: English. Do you have a question about the Zebra DS8178 or do you need help?Ask your question hereBelow you will find the product specifications and the manual specifications of the Zebra DS8178.The Zebra DS8178 is a handheld barcode reader with dimensions measuring 168 millimeters in height, 107 millimeters in depth, and 66 millimeters in width. With a weight of 235.3 grams, it is relatively lightweight. The reader operates at a wavelength of 617 nanometers and utilizes a photo diode sensor type. Rated with an International Protection (IP) code of IP42, the DS8178 provides limited protection against dust and water. It is designed to be reliable and durable, ensuring longevity in various environments. As a handheld device, the Zebra DS8178 is specifically created for barcode scanning purposes. Equipped with advanced technology, it is capable of accurately scanning barcodes of different types. Potential areas of use for this barcode reader include retail, manufacturing, healthcare, and logistics, among others. Designed to meet the demands of various industries, the DS8178 is suitable for both indoor and outdoor applications. The Zebra DS8178 excels in providing accurate barcode scanning, contributing to increased efficiency in business operations. With its lightweight and compact design, it offers comfort and ease of use for extended periods. This barcode reader is ideal for individuals and organizations seeking a powerful yet portable scanning device. Its reliable performance ensures barcode accuracy and enhances productivity in any working environment. In conclusion, the Zebra DS8178 is a compact and durable handheld barcode reader that excels in providing accurate scanning of various types of barcodes. With its lightweight design and advanced technology features, it offers comfort and efficiency for prolonged use in multiple industries.Operating temperature (T-T) 0 - 50 °CConnectivity technology Wired & WirelessPower source type BatteryBrandZebraModelDS8178 | DS8178-SR0F007ZZWKProductbarcode readersLanguageEnglishFiletypeUser manual (PDF)Product color BlackInternational Protection (IP) code IP42Housing material -Height 168 mmDepth 107 mmWidth 66 mmWeight 235.3 gWavelength 617 nmSensor type Photo diodeTilt reading angle 0 - 360 °Pitch reading angle 0 - 60 °Yaw reading angle 0 - 60 °Type Handheld bar code readerLinear (1D) barcodes supported -2D (matrix & stacked) barcodes supported -Scanner type 1D/2DWorking distance 610 mmOptical sensor resolution 1280 pixelsOperating temperature (T-T) 0 - 50 °CStorage temperature (T-T) -40 - 70 °COperating relative humidity (H-H) 5 - 95 %Connectivity technology Wired & WirelessStandard interfaces USB, RS-232, BluetoothBluetooth version 4.0Wireless range 100 mPC connection RS-232/USBPower source type BatteryBattery capacity 2500 mAhBattery technology Lithium-Ion (Li-Ion)Battery life 83 h show moreCan't find the answer to your question in the manual? You may find the answer to your question in the FAQs about the Zebra DS8178 below.To pair your Zebra DS8178, you can access the Bluetooth settings on your device and search for available devices. Once you find the DS8178, select it to establish the pairing.You can customize the scanning settings by scanning specific configuration barcodes. These barcodes contain commands to modify settings such as barcode type compatibility, prefix and suffix characters, and scanning modes.Yes, you can adjust the beeper volume of the DS8178 scanner. By scanning the appropriate barcodes in the user manual, you can set the volume to your desired level.Absolutely! The Zebra DS8178 barcode reader is compatible with iOS devices. Simply enable Bluetooth on your iOS device and follow the pairing instructions to connect the DS8178 effortlessly.To replace the battery of the DS8178, you can remove the battery door located on the back of the device. Inside, you will find the battery pack, which can be easily replaced by disconnecting the old battery and connecting the new one securely.The sensor type of the Zebra DS8178 is a photo diode. This ensures accurate scanning of barcodes for the user.The International Protection (IP) code of the Zebra DS8178 is IP42. This means that it is protected against dust ingress and is also resistant to dripping water when tilted at an angle up to 15 degrees.The Zebra DS8178 has both wired and wireless connectivity technology. This allows the user to choose the most convenient option for their specific needs.The Bluetooth version of the Zebra DS8178 is 4.0. This ensures a stable and reliable wireless connection for seamless barcode scanning.The wireless range of the Zebra DS8178 is 100 meters. This provides the user with flexibility and freedom of movement while scanning barcodes within a large area.The Zebra DS8178 has a weight of 235.3 g.The Zebra DS8178 has a height of 168 mm.The Zebra DS8178 has a width of 66 mm.The Zebra DS8178 has a depth of 107 mm.Yes, the manual of the Zebra DS8178 is available in English .Is your question not listed? Ask your question here